

**Amendments to the Claims:**

**Listing of Claims:**

1. (Previously Presented) A drop emitting device comprising:

a first linear array of side by side substantially mutually parallel first columnar arrays of drop emitting nozzles, the first linear array extending along an X-axis, and the first columnar arrays being oblique to the X-axis;

each first columnar array of drop emitting nozzles comprised of a first linear sub-column of N nozzles that is interleaved with and substantially parallel to an associated second linear sub-column of N nozzles so as to form N first pairs of nozzles, wherein each first pair of nozzles includes a nozzle from the first linear sub-column and an adjacent nozzle from the second linear sub-column, and wherein N is greater than 1;

wherein the nozzles of each first pair of nozzles are aligned along the X-axis and substantially parallel to a Y-axis that is orthogonal to the X-axis;

wherein the first linear sub-columns of nozzles emit drops of a first color and the second linear sub-columns of nozzles emit drops of a second color;

a second linear array of side by side substantially mutually parallel second columnar arrays of drop emitting nozzles, the second linear array extending along the X-axis and being adjacent the first linear array along a Y-axis that is orthogonal to the X-axis, and the second columnar arrays being oblique to the X-axis;

each second columnar array having an associated first columnar array displaced therefrom along the Y-axis;

each second columnar array of drop emitting nozzles comprised of a third linear sub-column of N nozzles that is interleaved with and substantially parallel to an associated fourth linear sub-column of N nozzles so as to form N second pairs of nozzles, wherein each second pair of nozzles includes a nozzle from the third linear sub-column and an adjacent nozzle from the fourth linear sub-column;

each second nozzle pair having an associated first nozzle pair displaced therefrom along the Y-axis;

wherein the nozzles of each second pair of nozzles are offset along the X-axis;

wherein the third linear sub-columns of nozzles emit drops of a third color and the fourth linear sub-columns of nozzles emit drops of a fourth color; and

wherein each of the first through fourth linear sub-columns has a nozzle pitch  $XP$  inches along the X-axis.

2. (Original) The drop emitting device of claim 1 wherein the first linear array of side by side substantially mutually parallel columnar arrays of drop emitting nozzles and the second linear array of side by side mutually parallel columnar arrays of drop emitting nozzles emit drops of melted solid ink.

3. (Original) The drop emitting device of claim 1 wherein each of the first through fourth sub-columns of nozzles has a nozzle pitch  $XP$  of at most about  $1/75$  inches along the X-axis.

4. (Original) The drop emitting device of claim 1 wherein each of the first through fourth sub-columns of nozzles has a nozzle pitch  $XP$  of at most about  $1/37.5$  inches along the X-axis.

5. (Original) The drop emitting device of claim 1 wherein the nozzles of each second pair of nozzles are offset along the X-axis by about  $XP/3$  inches.

6. (Original) The drop emitting device of claim 1 wherein the nozzles of each second pair of nozzles are offset along the X-axis by at most about .005 inches.

7. (Original) The drop emitting device of claim 1 wherein one of the nozzles of each second pair of nozzles is aligned along the X-axis with the associated first pair of nozzles.

8. (Original) The drop emitting device of claim 1 wherein the first and second colors are cyan and magenta.

9. (Original) The drop emitting device of claim 1 wherein the third and fourth colors are yellow and black.

10. (Original) The drop emitting device of claim 1 wherein:  
the first and second colors are cyan and magenta;  
the third and fourth colors are yellow and black; and  
each second nozzle pair is offset relative to its associated first nozzle pair along the X-axis.

11. (Original) The drop emitting device of claim 1 further including:  
a first plurality of finger manifolds fluidically coupled to the first linear sub-columns of nozzles;  
a second plurality of finger manifolds fluidically coupled to the second linear sub-columns of nozzles;  
a third plurality of finger manifolds fluidically coupled to the third linear sub-columns of nozzles; and  
a fourth plurality of finger manifolds fluidically coupled to the fourth linear sub-columns of nozzles.

Application No. 10/944,581

12. (Canceled)

13. (Canceled)

14. (Canceled)

15. (Canceled)

16. (Canceled)

17. (Canceled)

18. (Canceled)

19. (Canceled)

20. (Canceled)